

## WEATHERWASH'S "CHARRED" PRODUCT OVERVIEW

Why waste hours applying primers, paints, and glazes when you can age wood in minutes? Weatherwash's Charred stain is a tannin-based reactive stain, that naturally ages wood. It is suitable for nearly all wood types and yields deep blackened charred color in minutes, instead of centuries. Unlike pigment based stains, latex paints, or oil-based stains. Charred won't compromise the wood's grain. Color results depend on wood species and will create a natural-looking result from plank to plank. Stain can be top coated to maintain color consistency.

**AGE INDEX** Turn wood into a beautiful charcoal black tones. For more intense weathering, apply multiple coats.

SPECIES Lightly weather all woods, especially pretty on hardwoods.

USE Interior use on wood walls, ceilings, floors, cabinetry, furniture, millwork, etc.

## **DIRECTIONS**

**WOOD PREP** Sand wood with the grain. Do not apply pretreaters.

**PRODUCT PREP** Mix stain well before and during use to ensure settled materials are re-dispersed. Do not thin. First, test and inconspicuous swatch. For best results, store and use only when temperature is between 60-90°F (16-32°C) and relative humidity is below 85%. Do not store in metal containers

**COVERAGE** 1 Gallon treats 400 sq. ft. of smooth wood.

**APPLICATION** Use a foam roller, brush or paint sprayer to apply one liberal coat of stain in the direction of the grain. Wood will absorb stain. Each species will turn its own darkest color. For exteriors, stain may be applied on site but avoid contact with concrete or siding. For darker results, multiple coats may be applied.

**DRYING TIME** Allow wood to dry 60 minutes. Longer dry times for damp/humid climates, rough sawn & soft woods.

**CLEAN UP** Easy soap and water clean-up.

**FINISHES** After a minimum of 1 hour apply your favorite Weatherwash topcoat per the directions on the can.

\( \rightarrow\) Water-Based

Top Coat Compatible

© Non Toxic

Commercial & Residential

**≋** Interior

