

◆ WEATHERWASH ◆

THE NATURAL WAY TO WEATHER WOOD

Weatherwash's EXTERIOR WOOD SEALER can be used to seal raw and Weatherwash Coatings stained wood. It contains nano-particles that help protect wood from within. Unlike traditional products, EXTERIOR WOOD SEALER has no polymers to sit on wood and eventually chip off over time. That means lasting wood protection from the inside out. It has both UV protection and anti-fungal properties. In addition, when dry it will hardly affect the look of reclaimed- looking wood! Sealer protects against slitting, cupping, warping from harsh weather conditions.

USE: USE Any Exterior Wood Surface, like Siding, Shingles, Fences, Decks, etc.

SPECIES For use on any wood species, less teak.

≡ No Sheen

💧 Water-Based

😊 Easy Clean Up

♻️ VOC Free

🏠 Exterior Use



DIRECTIONS

WOOD PREP Apply to any raw, reclaimed, or Weatherwash stained wood. When using with traditional wood stains and sealers, apply EXTERIOR SEALER beneath polymer based coatings.

PRODUCT PREP PREPARATION Mix Well. Use when air (ambient) temperature is between 60-90°F (16-32°C) and relative humidity is below 85%.

COVERAGE 1 Quart treats 100 SQ FT of smooth wood.

APPLICATION Use a brush, paint sprayer, or flood system to apply one liberal coat in the direction of the grain. DRENCH the wood evenly to ensure consistent color. Do NOT apply and wipe off. Make sure to protect all sides of wood, especially cut edges. For exteriors, may be applied on site, and will not a harm ground or plant life.

DRYING TIME Allow to air dry for 24 hours. Apply a second coat approximately 24 hours later.

CLEAN UP Easy soap and water clean up.

WOOD CARE Annual application rejuvenates the wood's surface and prevents desaturation.